Cable for Underground Installation KC-OKB



Application

Rodent-proof cable

Armor

Water-resistant

Outdoor itstallation

High tensile strength

For manual or mechanical installation in soils of all categories, except soils tend to negative temperature deformations, in case of high requirements for resistance to mechanical loads, in sewage systems, protective pipes, blocks, collectors.

Specifications

Code of cable type	6032	6033	6054	6051	6055
Number of fibers	20	30	24	48	
Number of loose tube	5		4		
Number of fibers in loose tube	4	6		12	
Short-term crush test, kN/cm (N/10cm)	0,55 (5500)	0,4 (4000)		0,5 (5000)	0,4 (4000)
Dynamic tensile strength, not less than, kN	13		9,2	8,1	12,5
Operating temperature, °C	– 40...+60 °C		– 50...+70 °C	– 40...+60 °C	– 50...+70 °C
Installation temperature, °C	– 10...+50 °C				
Cable outer diameter, mm	11,9	12,5	11,4	14,1	12,4

ТОО «Kazcentrelectroprovod»
(Казцентрэлектропровод)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«Kazcentrelectroprovod» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501

e-mail
info@kcep.kz

web
www.kcep.kz