
Armored Cable Mini with Glass Yarns A-DQ(ZN)B2Y max. 144 Fiber



Application

- Rodent-proof cable
- For installation in cable duct system
- Dielectric
- Water-resistant
- Outdoor itstallation

Optical fiber cable for duct and micro duct installation by blowing.

Specifications

Code of cable type	10114	10115	10116	10117	6305
Number of fibers	12-60	12-72	12-96	12-144	12-144
Number of loose tube	1 ... 5	1 ... 6	1 ... 8	1 ... 12	1 ... 12
Number of fillers	4 ... 0	5 ... 0	7 ... 0	11 ... 0	11 ... 0
Cable outer diameter, mm	11,0±0,2	11,5±0,2	13,0±0,3	16,0±0,35	11,6±0,3
Fiber type, µm	250				
Minimum bending radius	20D				
Installation tensile strength, N	4 000				2 000
Operating temperature, °C	-40 ... +60 °C				-30 ... +60 °C
Installation temperature, °C	-10 ... +50 °C				-10 ... +50 °C

ТОО «Kazcentrelectroprovod»
(Казцентрэлектропровод)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«Kazcentrelectroprovod» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501
e-mail
info@kcep.kz
web
www.kcep.kz