A-DQ(ZN)2Y max. 24 Fiber



Application

- For installation in cable duct system
- Dielectric
- Water-resistant
- Air blow
- Outdoor itstallation

Optical fiber micro cable for duct and micro duct installation by blowing.

Specifications

Code of cable type	7201/7203	7204	7205	7207	7206
Number of fibers	2-12		2-24		
Cable outer diameter, mm	2,4±0,2	3,5±0,2	3,8±0,2	2,4±0,2	2,9±0,2
Fiber type, µm	200/250			200	
Minimum bending radius	15D				
Installation tensile strength, N	200		300	200	250
Operating temperature, °C	-20 ... +70				
Installation temperature, °C	-10 ... +60				
Microtube, OD/ID	7/4		10/6	7/4	10/6

ТОО «Kazcentrelectroprovod»
(Казцентрэлектропровод)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«Kazcentrelectroprovod» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501

e-mail
info@kcep.kz

web
www.kcep.kz