A-DQ(ZN)2Y max. 288 Fibers



Application

For installation in cable duct system

Dielectric

Air blow

Outdoor itstallation

Optical fiber mini cable for microduct installation by blowing.

Specifications

Code of cable type	10147	10102	10154	10124a	1091
Number of fibers/loose tube	12-288/1 ... 24				24-288/1 ... 12
Type of outer sheath	UV-resistant PE/PA				
Number of fillers	23 ... 0				11 ... 0
Max. cable outer diameter, mm	7,5±0,2	7,9±0,2	8,6±0,2	9,2±0,2	8,0±0,2
Fiber type, µm	200		250		200
Minimum bending radius	20D				
Installation tensile strength, N	2 000		2 500		3 500
Operating temperature, °C	-20 ... +70				
Installation temperature, °C	-10 ... +50		-15 ... +50		
Microtube, OD/ID	14/10		16/12		14/10

ТОО «КСЕР» (КСЭП)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«KCEP» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501

e-mail
info@kcep.kz

web
www.kcep.kz