Flat cable max. 48 Fibers







Application

Dielectric

Water-resistant

Air blow

Outdoor itstallation

Self-support aerial installation cable with FRP rods (f
suspension between communication poles, for instal
racks, on the walls of building in case of absence risk
damages.

Specifications

Code of cable type	1221	1222	1223	1201	1210	1224	1225
Number of fibers, up to	2	4	16		24		48
Number of loose tube	1				2	1	2
Number of fibers in loose tube, up to	2	4	16		24		
Short-term crush test, kN/cm	0,5	1,0		0,8	0,4	1,0	0,4
Dynamic tensile strength, not less than, kN	0,6	–		1,5	–		
Maximum permissible tensile load, kN	0,25	0,7	0,9	–	1,1		1,4
Operating temperature, °C	-50 ... +70			-40 ... +70	-40 ... +60	-50 ... +70	-40 ... +60
Installation temperature, °C	-10 ... +50						
Overall dimensions, thickness x height, mm	2,4x5,2	2,8x6,5	3,6x7,2	5,5x8,0	3,6x11,0	3,6x8,1	4,5x10,5

ТОО «КСЕР» (КСЭП)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«KCEP» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501

e-mail
info@kcep.kz

web
www.kcep.kz