A-DQ(ZN)B2Y max. 96 Fibers



Application

- Rodent-proof cable
- For installation in cable duct system
- Dielectric
- Armor
- Water-resistant
- Outdoor itstallation

Armored optical fiber mini cable with glass yarns for cabling ducts and utility tunnels.

Specifications

Code of cable type	6329	6308	6326
Number of fibers/loose tube	12-96/1 ... 8		
Type of outer sheath	UV-resistant PE		
Number of fillers	7 ... 0		
Max. cable outer diameter, mm	11,1±0,2	12,1±0,2	13,0±0,2
Fiber type, µm	250		
Minimum bending radius	20D		
Installation tensile strength, N	3 000	3 500	7 000
Operating temperature, °C	-40 ... +70		
Installation temperature, °C	-10 ... +50		

ТОО «КСЕР» (КСЭП)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«KCEP» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501
e-mail
info@kcep.kz
web
www.kcep.kz