Unshielded LAN Cable for Indore Installation U/UTP







Application

Indoor itstallation

Halogen-free

Cable for structured cable systems for indoor installation with a signal transmission frequency up to 100MHz (Cat.5e), or up to 250MHz (Cat.6).

Specifications

Electrical characteristics	Value
Number of pairs	25
Current-carrying conductor	soft cooper wire
Core diameter	up 0,48 to 0,51 mm
Twisted type	pairing
Minimum bending radius	55
Tensile strength, not less than, kN	0,4
Short-term crush test, kN/cm	40
Sheath type	PVC – sheath made of PVC
	LSZH – sheath from LSZH – Low Smoke Zero Halogen
Operating temperature, °C	-40 ... +60
Installation temperature, °C	-10 ... +50
Max. cable outer diameter max, mm	13,5

ТОО «КСЕР» (КСЭП)
Республика Казахстан
Карагандинская область
M22E7B8, город Сарань
Улица Шахтерская, дом 30 «А»
БИН 070340007238

«KCEP» LLP
30 «A», Shakhterskaya street
Saran, M22E7B8
Karaganda region
Republic of Kazakhstan
BIN 070340007238

tel./fax
+7 (7212) 912-501

e-mail
info@kcep.kz

web
www.kcep.kz