TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	A-DQ(ZN)2Y (16-18)x24-G.652.D/G.657.A1-200-10118								
Cable construction									
	1. Outer sheath: UV-resistant PE								
_	2. Water-blocking element of core: Water-swellable yarn								
•	3. Optical loose tube: 1,75mm PBT Tube								
4. Intramodule compound: Thix	· ·								
5. Optical Fiber: 200mkm Single									
6. Central strength element: Gla	•	P-E							
7. Rip-cord: Water-swellable yarn									
Temperature ranges	Storage and transportation	Installation	Operating						
	temperature	temperature	temperature						
	from -40 to +70 °C								
Resistance to water	from -40 to +70 °Cfrom -10 to +50 °Cfrom -20 to +60 °CWater resistant								
penetration									
Relative humidity at +35 ^o C, %	98								
Outer diameter, mm	9,4±0,2								
Average weight of 1 km of the	83±5%								
cable, kg									

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN Dynamic	2
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,05 (500)
Resistance to axial torsion at angle ±180° on 2 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

 $^{^{1}\}ensuremath{\,{\rm Tensile}}$ strength value is for maximum number of fibers design

3. Packaging and marking

Cable factory length, km	6
Package	Drum №14 (1401x813x1401)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.

Layer 1					Layer2							
1	2	3	4	5	6	1	2	3	4	5	6	
red	green	blue	yellow	white	slate	red	green	blue	yellow	white	slate	
Layer 2												
	7	8 9 10			11		12					
b	rown	\	violet	á	aqua	black		0	orange		pink	

5. Product data

Fiber count	384	432
Loose tubes x fibers	16x24	18x24