# TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### 1. Cable construction

Cable type	ble type A-DQ(ZN)4Y (16-24)x12-G.652.D-1074								
Cable construction 1. Outer sheath: PA 2. Optical loose tube: 1,95mm P 3. Optical Fiber: Single-mode Fik 4. Intramodule compound: Thixe 5. Water-blocking element of co 6. Insulation of central strength 7. Central strength element: Gla 8. Rip-cord: Water-swellable yar	per according to ITU-T G.652.D otropic compound ore: Water-swellable yarn element:PE iss reinforced plastic 2,6mm FR	P-E with insulation up to	3,8mm						
Temperature ranges	Storage and transportation	Installation	Operating						
	temperature	temperature	temperature						
	from -40 to +70 °C from -5 to +50 °C from -30 to +70 °C								
Resistance to water		Water resistant							
penetration									
Relative humidity at +35 <sup>0</sup> C, %	98								
Outer diameter, mm	13,75±0,2								
Average weight of 1 km of the cable, kg		130±5%							

#### 2. Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN Dynamic	3
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,3 (3000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 10 J	Resistant

 $<sup>^{1}\</sup>ensuremath{\,{\rm Tensile}}$  strength value is for maximum number of fibers design

### 3. Packaging and marking

Cable factory length, km	6
Package	Drum №18 (1820x1175x1820)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

### 4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

	Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural. "+m"- denotes single black stripe marking via co-extrusion, white stripe marking for black loose tube.										
Layer 1							Layer 2				
1	2	3	4	5	6	7	8	9	1	2	3
red	green	blue	yellow	white	slate	brown	violet	aqua	red	green	blue
	Layer 2										
4	5	6	7	8	9	10	11	12	13	14	15
yellow	white	slate	brown	violet	aqua	black	orange	pink	<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>

# 5. Product data

Fiber count	192	216	288
Loose tubes x fibers	16x12	18x12	24x12