TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	A-DQ(ZN)B2Y-(1-8)x12-G.652.D/G.657.A1-6326				
		$ \begin{array}{c} 1\\ 2\\ 3\\ -4\\ 5\\ 6\\ 7\\ 8\\ 9\\ 10\\ \end{array} $			
 Optical loose tube: 2,7m Intramodule compound Optical Fiber: Single-mo Central strength element Insulation of central strength 	ng strength element: Water swo nm PBT Tube : Thixotropic compound de Fiber according to ITU-T G.6 nt: Glass reinforced plastic 2,5m ength element: PE t of core: Water-swellable yarn	52.D and G.657.A1 nm FRP-E with insulation (up to 4,4 mm		
Temperature ranges	Storage and transportation temperature	Installation temperature	Operating temperature		
	from -40 to +70 °C	from -10 to +50 °C	from -40 to +60 °C		
Resistance to water penetration	Water resistant				
Relative humidity at +35 ^o C, %	98				
Outer diameter, mm	13,0±0,2				
Average weight of 1 km of the cable, kg130±5%					

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	7
Dynamic	/
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,5 (5000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 10 J	Resistant

 $^{^{1}\ \}mathrm{Tensile}\ \mathrm{strength}\ \mathrm{value}\ \mathrm{is}\ \mathrm{for}\ \mathrm{maximum}\ \mathrm{number}\ \mathrm{of}\ \mathrm{fibers}\ \mathrm{design}$



3. Packaging and marking

Cable factory length, km	6
Package	Drum №18 (1870x1170x1870)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural. 1 2 3 4 5 6 7 8 slate blue yellow white brown violet red green

5. Product data

Fiber count	12	24	48	60	72	84	96
Loose tubes x fibers	1x12	2x12	4x12	5x12	6x12	7x12	8x12