


TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	A-DQ(ZN)B4Y-(1-8)x12-G.652.D/G.657.A1-200-6308		
			
<p>Cable construction</p> <ol style="list-style-type: none"> 1. Outer sheath: PA 2. Strength element of core: Water swellable glass yarn 3. Optical loose tube: 2,3mm PBT Tube 4. Intramodule compound: Thixotropic compound 5. Optical Fiber: 200 mkm Single-mode Fiber according to ITU-T G.652.D and G.657.A1 6. Insulation of central strength element: PE 7. Central strength element: Glass reinforced plastic 2,6mm FRP-E with insulation up to 3,7mm 			
Temperature ranges	Storage and transportation temperature	Installation temperature	Operating temperature
	from -40 to +70 °C	from -10 to +50 °C	from -40 to +60 °C
Resistance to water penetration	Water resistant		
Relative humidity at +35° C, %	98		
Outer diameter, mm	12,1±0,2		
Average weight of 1 km of the cable, kg	124±5%		

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN Dynamic	3,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,3 (3000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle ± 90° with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 10 J	Resistant

¹ Tensile strength value is for maximum number of fibers design

3. Packaging and marking

Cable factory length, km	6
Package	Drum №17 (1715x955x1715)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.							
1	2	3	4	5	6	7	8
red	green	blue	yellow	white	slate	brown	violet

5. Product data

Fiber count	24	48	72	96
Loose tubes x fibers	2x12	4x12	6x12	8x12