# TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### 1. Cable construction

Cable type	ble type A-DQ(ZN)B4Y 18x12-G.652.D-6309						
		$ \begin{array}{c} 1\\ 2\\ 3\\ 4\\ 5\\ 6\\ 7\\ 9\\ 8\\ \end{array} $					
Cable construction							
1. Outer sheath: PA							
2. Strength element of core: Wa	ter swellable glass yarn						
3. Optical loose tube: 2,0mm PB							
4. Intramodule compound: Thix							
5. Optical Fiber: Single-mode Fib	-						
6. Water-blocking element of co	•						
7. Central strength element: Gla	ss reinforced plastic 2,0mm FR	P-E					
8. Core filler: PE							
9. Rip-cord: Water-swellable yar	'n						
Temperature ranges	Storage and transportation	Installation	Operating				
	temperature	temperature	temperature				
	from -40 to +70 °C	from -15 to +50 °C	from -30 to +70 °C				
Resistance to water	Water resistant						
penetration							
Relative humidity at +35 <sup>o</sup> C, %	98						
Outer diameter, mm	13,8±0,2						
Average weight of 1 km of the cable, kg	153±5%						

# 2. Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN	2
Dynamic	3
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,3 (3000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 15 J	Resistant

 $<sup>^{1}\ \</sup>mathrm{Tensile}\ \mathrm{strength}\ \mathrm{value}\ \mathrm{is}\ \mathrm{for}\ \mathrm{maximum}\ \mathrm{number}\ \mathrm{of}\ \mathrm{fibers}\ \mathrm{design}$ 

### 3. Packaging and marking

Cable factory length, km	6
Package	Drum №18b (1820x1375x1820)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

### 4. Coloring

Colorin	g of fibers i	n loose tu	be (Accor	ding to Cu	stomer's	requirem	ents color	can be di	fferent).		
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.

	Layer 1					Layer2						
1	2	3	4	5	6	1	2	3	4	5	6	
red	green	blue	yellow	white	slate	red	green	blue	yellow	white	slate	
	Layer 2											
	7	8 9			10		11		12			
b	rown	v	iolet	ć	aqua	ł	black		orange		pink	

#### 5. Product data

Fiber count	216
Loose tubes x fibers	18x12