

TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	A-D(ZN)4Y-24-200-652D/657A1-7207		
<p>Cable construction</p> <ol style="list-style-type: none"> Outer sheath: PA Strength element of core: aramid yarns The first layer of the loose tube: PC The second layer of the loose tube: PBT <p>Optical loose tube: 2,0 mm PBT\PC Tube</p> <ol style="list-style-type: none"> Intramodule compound: Thixotropic compound Optical Fiber: 200 mkm Single-mode Fiber according to ITU-T G.652.D and G.657.A1 			
Temperature ranges	Storage and transportation temperature	Installation temperature	Operating temperature
	from -20 to +70 °C	from -10 to +60 °C	from -20 to +70 °C
Resistance to water penetration	Water resistant		
Relative humidity at +35° C, %	98		
Outer diameter, mm	2,4±0,2		
Average weight of 1 km of the cable, kg	6±5%		

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	0,2
Dynamic	
Minimum bending radius	15D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 1 m length cable	Resistant
Resistance to bends at angle ± 90° with a radius equal to 15 nominal cable diameters	Resistant
Resistance to impact 2 J	Resistant

¹ Tensile strength value is for maximum number of fibers design

3. Packaging and marking

Cable factory length, km	6
Package	Coil OKKO №1 (495x445x495)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different). M-fiber with black ring mark.

1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink
13	14	15	16	17	18	19	20	21	22	23	24
<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>	<u>yellow+m</u>	<u>white+m</u>	<u>slate+m</u>	<u>brown+m</u>	<u>violet+m</u>	<u>aqua+m</u>	transparent	<u>orange+m</u>	<u>pink+m</u>

5. Product data

Fiber count	24
Loose tubes x fibers	1x24