## TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### 1. Cable construction

Cable type	A-DQ(ZN)B2Y-(1-12)x12-G.652.D-6305														
1															
2															
3															
5															
5 6 7															
								8							
								9							
10															
Cable construction															
1. Outer sheath:UV-resistant PE															
2.Strength element of core: Wa															
3. Optical loose tube: 1,85mm F															
4. Intramodule compound: Thix 5. Optical Fiber: Single-mode Fi															
6. Insulation of central strength	÷														
7. Central strength element: Gla		P-F with insulation up to	5 5mm												
8. Water-blocking element of c	•		5,51111												
9. Rip-cord: Water-swellable ya	-														
10. Core filler: PE															
Temperature ranges	Storage and transportation	Installation	Operating												
	temperature	temperature	temperature												
	from -40 to +70 °C	from -10 to +50 °C	from -30 to +60 °C												
Resistance to water	Water resistant														
penetration															
Relative humidity at +35° C, %	98														
Outer diameter, mm	11,6±0,2														
Average weight of 1 km of the	105±5%														
cable, kg															

### 2. Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN Dynamic	3
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,2 (2000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle ± 90° with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

 $<sup>^{1}\ \</sup>mathrm{Tensile}\ \mathrm{strength}\ \mathrm{value}\ \mathrm{is}\ \mathrm{for}\ \mathrm{maximum}\ \mathrm{number}\ \mathrm{of}\ \mathrm{fibers}\ \mathrm{design}$ 

# 3. Packaging and marking

Cable factory length, km	6
Package	Drum №14g (1401x1013x1401)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

### 4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).												
1	1	2	3	4	5	6	7	8	9	10	11	12
re	ed	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural. 1 2 3 4 5 6 7 8 9 10 11 12  $\operatorname{red}$ green blue yellow white slate violet aqua black pink brown orange

## 5. Product data

Fiber count	12	24	48	96	144
Loose tubes x fibers	1x12	2x12	4x12	8x12	12x12