


## TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### 1. Cable construction

Cable type	A-DQ(ZN)2Y (16-24)x12-G.652.D/G.657.A1-200-10124a		
			
<p>Cable construction</p> <ol style="list-style-type: none"> <li>1. Outer sheath: UV-resistant PE</li> <li>2. Optical loose tube: 1,4mm PBT Tube</li> <li>3. Intramodule compound: Thixotropic compound</li> <li>4. Optical Fiber: 200 mkm Single-mode Fiber according to ITU-T G.652.D and G.657.A1</li> <li>5. Water-blocking element of core: Water-swellable yarn</li> <li>6. Central strength element: Glass reinforced plastic 2,8mm FRP-E</li> <li>7. Rip-cord: Water-swellable yarn</li> </ol>			
Temperature ranges	Storage and transportation temperature	Installation temperature	Operating temperature
	from -20 to +70 °C	from -15 to +50 °C	from -20 to +70 °C
Resistance to water penetration	Water resistant		
Relative humidity at +35° C, %	98		
Outer diameter, mm	9,2±0,2		
Average weight of 1 km of the cable, kg	73±5%		

### 2. Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN	
Dynamic	2,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 2 m length cable	Resistant
Resistance to bends at angle ± 90° with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 5 J	Resistant

<sup>1</sup> Tensile strength value is for maximum number of fibers design

### 3. Packaging and marking

Cable factory length, km	6
Package	Drum №14 (1401x813x1401)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

### 4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).

1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural. "+m"- denotes single black stripe marking via co-extrusion, white stripe marking for black loose tube.

Layer 1									Layer 2		
1	2	3	4	5	6	7	8	9	1	2	3
red	green	blue	yellow	white	slate	brown	violet	aqua	red	green	blue
Layer 2											
4	5	6	7	8	9	10	11	12	13	14	15
yellow	white	slate	brown	violet	aqua	black	orange	pink	<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>

### 5. Product data

Fiber count	192	216	288
Loose tubes x fibers	16x12	18x12	24x12