## TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### 1. Cable construction

Cable type	A-DQ(ZN)4Y (16-24)x12-G.652.D/G.657.A1-200-10124a							
Cable construction 1. Outer sheath: PA 2. Optical loose tube: 1,4mm PB 3. Intramodule compound: Thixe 4. Optical Fiber: 200 mkm Single 5. Water-blocking element of co 6. Central strength element: Gla 7. Rip-cord: Water-swellable yar	otropic compound mode Fiber according to ITU- <sup>-</sup> re: Water-swellable yarn ss reinforced plastic 2,8mm FR							
Temperature ranges	Storage and transportation	Installation	Operating					
	temperature	temperature	temperature					
	from -20 to +70 °C	from -15 to +50 °C	from -20 to +70 °C					
Resistance to water	Water resistant							
penetration								
Relative humidity at +35 <sup>0</sup> C, %	98							
Outer diameter, mm	9,2±0,2							
Average weight of 1 km of the cable, kg	73±5%							

#### 2. Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN	
Dynamic	2,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 2 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

 $<sup>^{1}\</sup>ensuremath{\,{\rm Tensile}}$  strength value is for maximum number of fibers design

# 3. Packaging and marking

Cable factory length, km	6
Package	Drum №14 (1401x813x1401)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

## 4. Coloring

C	Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is											
natural.	natural. "+m"- denotes single black stripe marking via co-extrusion, white stripe marking for black loose tube.										
	Layer 1								Layer 2		
1	2	3	4	5	6	7	8	9	1	2	3
red	green	blue	yellow	white	slate	brown	violet	aqua	red	green	blue
	Layer 2										
4	5	6	7	8	9	10	11	12	13	14	15
yellow	white	slate	brown	violet	aqua	black	orange	pink	<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>

### 5. Product data

Fiber count	192	216	288
Loose tubes x fibers	16x12	18x12	24x12