

PRELIMINARY TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	A-DQ(ZN)4Y-(4-6)x24-200-652D/657A1-1067
	1 2 3 4 5 6 7 8

Cable construction

1. Outer sheath: PA

2. Optical loose tube: 2,3mm PBT Tube

3. Intramodule compound: Thixotropic compound

4. Optical Fiber: 200 mkm Single-mode Fiber according to ITU-T G.652.D and G.657.A1

5. Rip-cord: Water-swellable yarn

6. Central strength element: Glass reinforced plastic 2,3mm FRP-E

7. Water-blocking element of core: Water-swellable yarn

8. Core filler: PE

Temperature ranges	Storage and transportation	Installation	Operating		
	temperature	temperature	temperature		
	from -40 to +70 °C	from -15 to +70 °C	from -40 to +70 °C		
Resistance to water	Water resistant				
penetration					
Relative humidity at +35° C, %	98				
Outer diameter, mm	7,8±0,2				
Average weight of 1 km of the	50±5%				
cable, kg					

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN Dynamic	1,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,12 (1200)
Resistance to axial torsion at angle ±360° on 1 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

¹ Tensile strength value is for maximum number of fibers design



3. Packaging and marking

Cable factory length, km	6	
Package	Drum №12a (1221x855x1221)	
Tolerance, %	±3,0	
Short lengths (customer approval)	Maximum 5%	
Marking method	Inkjet printing	
The accuracy of marking, %	±0,5	

4. Coloring

Colorir	Coloring of fibers in loose tube (According to Customer's requirements color can be different). M-fiber with										
black r	black ring mark.										
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink
13	14	15	16	17	18	19	20	21	22	23	24
<u>red+m</u>	green+m	<u>blue+m</u>	vellow+m	white+m	slate+m	brown+m	<u>violet+m</u>	agua+m	transparent	orange+m	pink+m

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is						
natural.						
1 2 3 4 5 6						
red	green	blue	yellow	white	slate	

5. Product data

Fiber count	96	144
Loose tubes x fibers	4x24	6x24