TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type A-DQ(ZN)B2Y-24x12-250-652D-6318							
		$ \begin{array}{c} 1\\ 2\\ 3\\ 4\\ 5\\ 6\\ 7\\ 8\end{array} $					
 Optical loose tube: 1,4n Intramodule compound Optical Fiber: Single-mo Water-blocking element 	e: Water swellable glass yarn nm PBT Tube : Thixotropic compound de Fiber according to ITU-T G.6 t of core: Water-swellable yarn nt: Glass reinforced plastic 2,8m						
Temperature ranges	Storage and transportation temperature from -40 to +70 °C	Installation temperature from -15 to +60 °C	Operating temperature from -30 to +70 °C				
Resistance to water penetration	Water resistant						
Relative humidity at +35 ⁰ C, %	98						
Outer diameter, mm	10,4±0,2						
Average weight of 1 km of the cable, kg90±5%							

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	2,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 2 m length cable	Resistant
Resistance to bends at angle \pm 90 ⁰ with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 5 J	Resistant

 $^{^{1}\}ensuremath{\,}^{1}$ Tensile strength value is for maximum number of fibers design

3. Packaging and marking

Cable factory length, km	6
Package	Drum №14 (1401x813x1401)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is											
natural.	natural. "+m"- denotes single black stripe marking via co-extrusion, white stripe marking for black loose tube.										
Layer 1							Layer 2				
1 2 3 4 5 6 7 8 9 1 2							3				
red	green	blue	yellow	white	slate	brown	violet	aqua	red	green	blue
Layer 2											
4	5	6	7	8	9	10	11	12	13	14	15
yellow	white	slate	brown	violet	aqua	black	orange	pink	<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>

5. Product data

Fiber count	288
Loose tubes x fibers	24x12