PRELIMINARY TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type A-DQ(ZN)B2Y-8x24-250-652D/657A1-6320							
A DOLENDET OXER 250 0520/05/AL 0520							
Cable construction							
1. Outer sheath: UV-resist	ant PE						
2. Peripheral water-blocki	ng strength element: Water sw	ellable glass yarn					
3. Optical loose tube: 2,5n	nm PBT Tube						
4. Intramodule compound	: Thixotropic compound						
5. Optical Fiber: Single-mo							
6. Insulation of central str	ength element: PE						
7. Central strength elemer	nt: Glass reinforced plastic 2,5m	nm FRP-E with insulation	up to 4,0mm				
8. Water-blocking elemen	t of core: Water-swellable yarn						
9. Rip-cord: Water-swellal							
Temperature ranges	Storage and transportation	Installation	Operating				
	temperature	temperature	temperature				
	from -40 to +70 °C from -10 to +50 °C		from -30 to +70 °C				
Resistance to water	Water resistant						
penetration							
Relative humidity at +35 ^o C, %	98						
Outer diameter, mm	12,8±0,2						
Average weight of 1 km of the	124±5%						
cable, kg	cable, kg						

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	4
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,15 (1500)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 15 J	Resistant

 $^{^{1}\ \}mathrm{Tensile}\ \mathrm{strength}\ \mathrm{value}\ \mathrm{is}\ \mathrm{for}\ \mathrm{maximum}\ \mathrm{number}\ \mathrm{of}\ \mathrm{fibers}\ \mathrm{design}$



3. Packaging and marking

Cable factory length, km	6
Package	Drum №17 (1715x955x1715)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Colorir	Coloring of fibers in loose tube (According to Customer's requirements color can be different). M-fiber										
with b	with black ring mark.										
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink
13	14	15	16	17	18	19	20	21	22	23	24
<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>	<u>vellow+m</u>	<u>white+m</u>	<u>slate+m</u>	<u>brown+m</u>	<u>violet+m</u>	<u>aqua+m</u>	<u>transparent</u>	orange+m	<u>pink+m</u>

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.

1	2	3	4	5	6	7	8
red	green	blue	yellow	white	slate	brown	violet

5. Product data

Fiber count	192
Loose tubes x fibers	8x24