TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	able type A-DQ(ZN)2Y4Y-12x12-250-652D-10126						
		$ \begin{array}{c} 1\\ 2\\ 3\\ 4\\ 5\\ 6\\ 7\\ 8\\ 9\\ \end{array} $					
 Insulation of central stre 7. Central strength element 	ant PE mm PBT Tube I: Thixotropic compound ode Fiber according to ITU-T G.6 ength element: PE nt: Glass reinforced plastic 2,5 m t of core: Water-swellable yarn	nm FRP-E with insulation	up to 6,6 mm				
Temperature ranges	Storage and transportation temperature from -40 to +70 °C	Installation temperature from -5 to +60 °C	Operating temperature from -40 to +70 °C				
Resistance to water penetration	Water resistant						
Relative humidity at +35 ^o C, %	98						
Outer diameter, mm	15,5±5%						
Average weight of 1 km of the cable, kg		187±5%					

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	2,5
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 5 J	Resistant

 $^{^{1}\ \}mathrm{Tensile}\ \mathrm{strength}\ \mathrm{value}\ \mathrm{is}\ \mathrm{for}\ \mathrm{maximum}\ \mathrm{number}\ \mathrm{of}\ \mathrm{fibers}\ \mathrm{design}$

3. Packaging and marking

Cable factory length, km	6
Package	Drum №18b (1870x1370x1870)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural. 1 2 3 4 5 6 7 8 9 10 11 12 black blue yellow white slate violet pink red green brown aqua orange

5. Product data

Fiber count	144
Loose tubes x fibers	12x12