PRELIMINARY TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

1. Cable construction

Cable type	Cable type A-DQ(ZN)2Y(SR)2Y-24x12-250-652D/657A1-24124							
		1 2 3 4 5 6 7 8 9						
7. Water-blocking element	steel tape Int PE Im PBT Tube : Thixotropic compound de Fiber according to ITU-T G.6 c of core: Water-swellable yarn it: Glass reinforced plastic 2,8m							
Temperature ranges	Storage and transportation temperature from -30 to +70 °C	Installation temperature from -15 to +50 °C	Operating temperature from -30 to +70 °C					
Resistance to water								
penetration								
Relative humidity at +35 ^o C, %	98							
Outer diameter, mm	13,0±0,2							
Average weight of 1 km of the cable, kg	162±5%							

2. Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	3,0
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,1 (1000)
Resistance to axial torsion at angle ±360° on 2 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

 $^{^{1}\}ensuremath{\,}^{1}$ Tensile strength value is for maximum number of fibers design

3. Packaging and marking

Cable factory length, km	6
Package	Drum №17 (1715x955x1715)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

4. Coloring

C	Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is											
natural.	natural. "+m"- denotes single black stripe marking via co-extrusion, white stripe marking for black loose tube.										
	Layer 1								Layer 2		
1	2	3	4	5	6	7	8	9	1	2	3
red	green	blue	yellow	white	slate	brown	violet	aqua	red	green	blue
	Layer 2										
4	5	6	7	8	9	10	11	12	13	14	15
yellow	white	slate	brown	violet	aqua	black	orange	pink	<u>red+m</u>	<u>green+m</u>	<u>blue+m</u>

5. Product data

Fiber count	192	216	288
Loose tubes x fibers	16x12	18x12	24x12