

TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

Cable construction

Cable type	A-DQ(ZN)2Y-(16-18)x24/A-DQ(ZN)4Y-(16-18)x24-10118			
Standards	IEC 60793, IEC 60794			
	1 2 3 4 5 6 7			

Cable construction

1. Outer sheath: UV-resistant PE/PA

2. Water-blocking element of core: Water-swellable yarn

3. Optical loose tube: PBT Tube

4. Intramodule compound: Thixotropic compound

5. Optical Fiber: 200µm Single-mode Fiber according to ITU-T G.652.D/G.657.A1

6. Central strength element: Glass reinforced plastic FRP-E

7. Rip-cord: Water-swellable yarn

Temperature ranges	Storage and transportation	Installation	Operating				
	temperature	temperature	temperature				
	from -40 to +70 °C	from -10 to +50 °C	from -20 to +70 °C				
Resistance to water		Water resistant					
penetration							
Relative humidity at +35° C, %	98						
Outer diameter, mm	9,4±0,2						
Average weight of 1 km of the	83±5%						
cable, kg							

Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	2
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,05 (500)
Resistance to axial torsion at angle ±180° on 2 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 5 J	Resistant

¹ Tensile strength value is for maximum number of fibers design



Packaging and marking

Cable factory length, km	6
Package	Drum №14 (1400x815x1400)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.																			
Layer 1 Layer2																			
1	2	3	4	5	6	1 2 3 4 5				6									
red	green	blue	yellow	white	slate	red	green	blue	yellow	white	slate								
	Layer 2																		
	7		8 9		9		10		10		10		10		10		11	12	
b	rown	١	violet .	i i	aqua		black		orange		nk								

Cable sheath coloring				
Sheath material	Р	E	PA	
Color	black	orange		

Product data

Fiber count	384	432
Loose tubes x fibers	16x24	18x24