

TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

Cable construction

Cable type	A-DQ(ZN)2Y-8x24-10135 A-DQ(ZN)2Y-8x24/A-DQ(ZN)4Y-8x24-10136
Standards	IEC 60793, IEC 60794
	2 3 4 5 6 7

Cable construction

1. Outer sheath: UV-resistant PE/PA

2. Optical loose tube: PBT Tube

3. Intramodule compound: Thixotropic compound

4. Optical Fiber: 200 μ m Single-mode Fiber according to ITU-T G.652.D/G.657.A1

5. Central strength element: Glass reinforced plastic FRP-E

6. Water-blocking element of core: Water-swellable yarn

7. Rip-cord: Water-swellable yarn

Temperature ranges	Storage and transportation	Installation	Operating	
	temperature	temperature	temperature	
	from -30 to +70 °C	from -15 to +50 °C	from -30 to +70 °C	
Resistance to water		Water resistant		
penetration				
Relative humidity at +35° C, %		98		
Outer diameter, mm		6,4±0,2		
Average weight of 1 km of the		43±5%		
cable, kg				

Mechanical characteristics

Calculated tensile strength, not less than ¹ , kN	
Dynamic	2
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,03 (300)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 2 J	Resistant

-

¹ Tensile strength value is for maximum number of fibers design



Packaging and marking

Cable factory length, km	6	
Package	Drum №10 (1000x630x1000)	
Tolerance, %	±3,0	
Short lengths (customer approval)	Maximum 5%	
Marking method	Inkjet printing	
The accuracy of marking, %	±0,5	

Coloring

Colorir	Coloring of fibers in loose tube (According to Customer's requirements color can be different). M-fiber with										
black r	black ring mark.										
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink
13	14	15	16	17	18	19	20	21	22	23	24
<u>red+m</u>	green+m	<u>blue+m</u>	<u>vellow+m</u>	white+m	slate+m	brown+m	<u>violet+m</u>	agua+m	transparent	orange+m	pink+m

Coloring of optical loose tube (According to Customer's requirements color can be different).							
1 2 3 4 5 6 7 8							
red	green	blue	yellow	white	slate	brown	violet

Cable sheath colo	ring		
Cable type	10136	10135	10136
Sheath material	F	PE	PA
Color	black orange orange		

Product data

Fiber count	192
Loose tubes x fibers	8x24