

### **TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE**

### **Cable construction**

Cable type	A-DQ(ZN)B2Y-(16-18)x12-6309
Standards	IEC 60793, IEC 60794

Cable construction

1. Outer sheath: UV-resistant PE

2. Strength element of core: Water swellable glass yarn

3. Optical loose tube: PBT Tube

4. Intramodule compound: Thixotropic compound

5. Optical Fiber: Single-mode Fiber according to ITU-T G.652.D or G.652.D/G.657.A1

6. Water-blocking element of core: Water-swellable yarn7. Central strength element: Glass reinforced plastic FRP-E

8. Core filler: PE

9. Rip-cord: Water-swellable yarn

Temperature ranges	Storage and transportation	Installation	Operating				
	temperature	temperature	temperature				
	from -40 to +70 °C	from -15 to +50 °C	from -30 to +70 °C				
Resistance to water	Water resistant						
penetration							
Relative humidity at +35° C, %	98						
Outer diameter, mm	13,1±0,2						
Average weight of 1 km of the	133±5%						
cable, kg							

## **Mechanical characteristics**

Calculated tensile strength, not less than <sup>1</sup> , kN	
Dynamic	3
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,3 (3000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle $\pm 90^{\circ}$ with a radius equal to 20 nominal	Resistant
cable diameters	
Resistance to impact 15 J	Resistant

<sup>&</sup>lt;sup>1</sup> Tensile strength value is for maximum number of fibers design



# Packaging and marking

Cable factory length, km	6
Package	Drum №17 (1700x965x1700)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

# Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).											
1	2	3	4	5	6	7	8	9	10	11	12
red	green	blue	yellow	white	slate	brown	violet	aqua	black	orange	pink

Coloring of optical loose tube (According to Customer's requirements color can be different). Core-filler color is natural.											
Layer 1						Layer 2					
1	2	3	4	5	6	1 2 3 4 5 6				6	
red	green	blue	yellow	white	slate	red	green	blue	yellow	white	slate
	Layer 2										
	7		8		9	10			11		2
b	rown	٧	riolet	á	aqua	black		orange		nk	

# **Product data**

Fiber count	192	216
Loose tubes x fibers	16x12	18x12