


## TECHNICAL DESCRIPTION OF FIBER OPTIC CABLE

### Cable construction

Cable type	A-DQ(ZN)B2Y-(4-24)-6211		
Standards	IEC 60793, IEC 60794		
			
<p>Cable construction</p> <ol style="list-style-type: none"> <li>1. Outer sheath: UV-resistant PE</li> <li>2. Water-blocking element of core: Water-swellable glass yarns</li> <li>3. The first layer of the loose tube: PBT</li> <li>4. The second layer of the loose tube: PC Optical loose tube: PBT\PC Tube</li> <li>5. Intramodule compound: Thixotropic compound</li> <li>6. Optical Fiber: Single-mode Fiber according to ITU-T G.652.D or G.652.D/G.657.A1</li> <li>7. Rip-cord: Synthetic yarn</li> </ol>			
Temperature ranges	Storage and transportation temperature	Installation temperature	Operating temperature
	from -40 to +70 °C	from -5 to +50 °C	from -40 to +70 °C
Resistance to water penetration	Water resistant		
Relative humidity at +35° C, %	98		
Outer diameter, mm	7,5±0,2		
Average weight of 1 km of the cable, kg	50±5%		

### Mechanical characteristics

Calculated tensile strength, not less than <sup>1</sup> , kN	
Dynamic	3
Minimum bending radius	20D
Short-term crush test, kN/cm (N/10cm)	0,3 (3000)
Resistance to axial torsion at angle ±360° on 4 m length cable	Resistant
Resistance to bends at angle ± 90° with a radius equal to 20 nominal cable diameters	Resistant
Resistance to impact 10 J	Resistant

<sup>1</sup> Tensile strength value is for maximum number of fibers design

## Packaging and marking

Cable factory length, km	6
Package	Drum №12a (1200x855x1200)
Tolerance, %	±3,0
Short lengths (customer approval)	Maximum 5%
Marking method	Inkjet printing
The accuracy of marking, %	±0,5

## Coloring

Coloring of fibers in loose tube (According to Customer's requirements color can be different).					
1	2	3	4	5	6
red	green	blue	yellow	white	slate

## Product data

Fiber count	4	6	12	24
Loose tubes x fibers	1x4	1x6	1x12	1x24